CENTRAL INTELLIGENCE AGENCY

620803

INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

25X1

•		by law. The reproduction of this form is prohibited.	
	CONFIDENTIAL		25
		25X1A	
COUNTRY	Indochina	REPORT NO.	
SUBJECT	Lao Dong Party Instructions on Concealment Techniques	DATE DISTR. 30 June 1954	+
	25X1C	NO. OF PAGES 2	
ATE OF I	NFO.	REQUIREMENT NO. RD	
LACE ACQ	UIRED	REFERENCES	
		1	
1 2	THE APPRAISAL OF CONT (FOR KEY SEE)		
•			
2.	time searching for them. The enemy makes reconnaissance of underwhich will betray the presence of underinto the hiding places but throw grent are often sent into the hiding places	erwater noises and searches for air vents erwater hiding places. They seldom descend ades through the air vents. War prisoners to search for us, but experience has the life of the prisoners, they do not	
	presence. The last person to descend arranging the bushes and branches prop		
	Hasty departures should be avoided. Coutside agents, and departure should be signs. Preferably, departure should be	Conventional signs must be arranged with be made only upon recognition of these be made only by prearrangement.	
	Consideration must be given to sanitate are to be occupied three to seven days through the inside and a pickaxe is not a pickaxe is not be a seven days.	tion facilities if underwater hiding places 3. Supplementary air vents can be drilled seeded for excavation.	

x FBI

AEC

CONFIDENTIAL

XX. AIR

X NAVY

STATE

X ARMY

Approved For Release 2003/08/06 : CIA-RDP80-00810A004301030007-3 25X1A				
CONFIDENTIAL/				25X1

-2-

- 6. Only those locations which afford natural cover and are least suspect should be selected. The walls should be sturdy and thick in order to avoid detection by thumping on the ground with pickaxes and iron rods. When conditions are favorable it is advantageous to have thin walls to permit quick exits.
- 7. A trench of at least forty centimeters should be constructed at the entrance in the event the hiding place is discovered and the enemy throw grenades through the entrance.
- 8. Hiding places should be constructed in a zig-zag pattern to avoid repercussions from grenades thrown through the entrance.
- 9. The entrance and the air vents must be well camouflaged. The air vents should be numerous and small in size. They should be tested to ensure proper functioning.
- 10. Hiding places should be constructed both inside and ouside of the villages. If there are hiding places outside the villages only, the combat morale of the guerrillas will be affected in their defense of the villages. Within the walls of the village, hiding places should be constructed away from the administrative centers.
- 11. Locations for hiding places outside the villages must be carefully selected to avoid areas where movement of enemy tanks will cause their collapse. Also to be avoided are locations where exposed approaches make detection of exit and entrance traces easy. Hiding places must be checked regularly and kept in usable condition at all times.
- 12. A preliminary assignment of responsibilities must be made to each person in the hiding places. Outside agents must be initially selected from among the mothers or wives of the guerrillas who are in the hiding places.
- 13. Where construction of an underwater hiding place leaves a detectable disturbed area, buffalo dung mixed with the water will calm the water within several hour.

CONFIDENTIAL/	